

SEED OR SOD TOPSOIL TO BE USED FOR TOP 12" IN YARDS

6" MIN.

12" MIN.

BACKFILL WITH TOPSOIL AND COMPACT AGAINST THE OUTSIDE SURFACE OF THE MANHOLE

NON-PAVED
NO PEDESTRIAN TRAFFIC

ABOVE GRADE CONSTRUCTION

SEED OR SOD TOPSOIL TO BE USED FOR TOP 12" IN YARDS

BACKFILL WITH TOPSOIL AND COMPACT AGAINST THE OUTSIDE SURFACE OF THE MANHOLE

12" MIN.

24" MIN.

FULL DEPTH SAW CUT TO NEAT LINE AND BREAKOUT PAVEMENT TOWARD CASTING

MATCH GRADE

CONCRETE COLLAR, SEE CONCRETE MANHOLE COLLAR DETAIL

SAND MATERIAL BACKFILL, COMPACTED

3' MIN.

NON-PAVED

PAVED

1" MIN. TO 2" MAX. IN PEDESTRIAN TRAFFIC AREAS
6" MIN. IN OTHER AREAS

AT GRADE CONSTRUCTION

TYPICAL EXCAVATION AND RESTORATION DETAIL

NOT TO SCALE

PATH NAME: /E1/PARTS/STD/DCN.STDS/408-EXCAV-REST-CONST.DGN LFM 05/25/2012

EXCAVATION AND RESTORATION AT GRADE AND ABOVE GRADE CONSTRUCTION	
CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT	
DRAWN BY: R.M.O. CHECKED BY: <i>HBS</i> DATE: MARCH 2022	APPROVED <i>[Signature]</i>
NOT TO SCALE	STANDARD NO. 408