



TREE ANCHOR LAYOUT PLAN

TOP OF ROOT BALL TO BE 2" BELOW PAVER FINISHED GRADE (THE EXPOSED ROOT FLARE OF THE TREE IS CONSIDERED TO BE THE TOP OF ROOT BALL)

CUT AND REMOVE ALL WIRE ROPE AND BURLAP FROM TOP OF ROOT BALL

STEEL ANCHOR CABLE

SHREDDED PINE BARK MULCH TO BE LEVEL WITH THE TOP OF PAVER

80 MM CONCRETE UNIT PAVER EQUAL TO UNI ECO-STONE

1" TO 1-1/2" SAND SETTING BED

GEOTEXTILE SOIL SEPARATOR FABRIC

2'-6" DEPTH CU STRUCTURAL SOIL

EXISTING SIDEWALK AND BASE

PROPOSED CONCRETE OR PAVER SIDEWALK

COMPACTED SUBGRADE TO 95% SPD

GROUND ANCHOR

CU STRUCTURAL SOIL UNDER PROPOSED PAVING TO LIMITS IDENTIFIED ON PLANS

NOTE:

1. EXCAVATE STRUCTURAL SOIL AS REQUIRED TO ACCOMMODATE TREE ROOT BALL.
2. GROUND ANCHORS EQUAL TO DUCKBILL EARTH ANCHORS MODEL #88 RBK STRAP. INSTALL PER MANUFACTURER'S RECOMMENDATIONS.
3. TREE GROUND ANCHORS TO BE DRIVEN TO DEEPEST POSSIBLE DEPTH (MINIMUM DEPTH OF 42").

TREE WELL WITHOUT TREE GRATE	
CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT	
DRAWN BY: R.M.O. CHECKED BY: <i>HAS</i> DATE: MARCH 2022	APPROVED 
NOT TO SCALE	STANDARD NO. 830